

PISTOL AND REVOLVER LOADS

Cartridge	Bullet Wt., gr. Type	Min. OAL, in.	Bullseye			Red Dot			Green Dot			Unique			Herco			Blue Dot			Hercules 2400			
			c.w. gr.	Vel., fps	c.u.p.	c.w. gr.	Vel., fps	c.u.p.	c.w. gr.	Vel., fps	c.u.p.	c.w. gr.	Vel., fps	c.u.p.	c.w. gr.	Vel., fps	c.u.p.	c.w. gr.	Vel., fps	c.u.p.	c.w. gr.	Vel., fps	c.u.p.	
.25 Auto.	50 FMC	0.875	1.3	760	15,000	1.3	770	15,500	1.4	785	15,400	1.7	760	14,800	1.7	735	15,600							
.32 Auto	71 FMC	0.984	2.2	835	12,500	2.4	850	12,800	2.5	800	11,000	2.5	820	11,200	3.2	880	13,500							
.32 S&W Long (.32 Colt New Police)	98 L	1.265	1.8	700	10,100	2.0	715	9,900	2.2	725	10,100	2.7	715	9,700	2.7	720	9,900							
.32 H&R Magnum	85 J	1.320	3.4	1,020	18,700	3.4	1,030	19,200	3.5	1,035	19,500	4.1	1,050	18,700	4.6	1,060	18,900	6.6	1,100	19,000				
	95 L	1.320	3.4	1,020	19,500	3.1	980	19,700	3.5	1,010	19,600	4.0	1,000	19,000										
9 mm Luger	95 FMC	1.070	4.8	1,200	27,600	4.7	1,200	27,800	5.0	1,200	28,800	5.7	1,225	27,600	5.8	1,200	27,000							
	115 FMC	1.050	4.0	1,115	28,100	4.0	1,115	28,700	4.4	1,140	29,000	5.2	1,210	29,500	5.2	1,185	29,200	6.8	1,130	27,500				
	124 FMC	1.100	4.5	1,075	27,600	4.0	1,065	26,900	4.2	1,060	27,500	4.8	1,100	28,100	5.5	1,075	26,700	8.0	1,185	29,500				
.357 Magnum Target Load	110 JHP	1.545	8.5	1,605	34,900	8.5	1,615	39,600	8.6	1,580	36,400	10.0	1,655	34,900	9.9	1,555	40,000	12.8	1,720	39,900	17.5	1,745	39,900	
	125 SJHP	1.570	8.3	1,515	39,200	7.8	1,465	40,000	8.0	1,435	38,800	9.3	1,515	39,500										
	146 LWC	1.525	3.5	830	10,200	3.7	840	11,300				4.5	805	9,900										
	146 LWC	1.525	7.4	1,390	39,900	6.3	1,275	37,500	7.0	1,335	39,900	8.0	1,380	37,200	8.5	1,420	38,400	10.5	1,515	39,800	15.0	1,615	39,900	
	158 LRN	1.600	7.0	1,295	34,300	6.5	1,200	36,000	7.5	1,300	36,100	8.5	1,385	36,500	9.0	1,405	38,200	11.0	1,425	35,200	15.0	1,560	39,500	
	158 JSP	1.565	7.4	1,295	40,000	7.0	1,225	38,100	7.6	1,290	37,900	8.0	1,285	38,400	8.3	1,300	39,400	10.5	1,445	39,300	14.5	1,465	38,800	
	170 FMC	1.550	6.0	1,120	38,900	5.6	1,050	38,400	6.0	1,065	38,000	6.9	1,155	39,100	7.0	1,140	38,500	10.0	1,345	39,700	13.0	1,335	39,700	
.38 Auto.	130 FMC	1.260	4.0	935	18,100	4.0	910	19,400	4.2	910	19,000	5.3	945	18,800	5.3	945	19,600	7.5	1,000	19,400				
.38 Super Auto.	115 JHP	1.255	5.5	1,150	26,100	5.3	1,205	27,700	5.5	1,180	27,700	6.5	1,200	29,000	6.2	1,190	28,000	8.5	1,210	27,100				
	130 FMC	1.255	4.8	1,100	27,200	4.8	1,110	29,200	4.9	1,060	28,400	5.8	1,100	27,300	6.0	1,140	28,700	8.0	1,150	27,600				
.38 Special Target Load	110 JHP	1.430	5.0	1,150	15,100	5.2	1,145	15,100	5.6	1,130	14,500	6.8	1,155	14,500	6.8	1,185	15,200	8.7	1,135	13,300				
	125 JSP	1.435	4.4	985	14,200	4.6	970	13,800	5.0	970	13,200	6.5	1,070	14,600	6.5	1,090	15,000	8.5	1,025	13,500				
	146 LWC	1.235	2.6	775	11,200	2.8	785	11,300	2.9	770	10,700	3.5	770	11,100	3.5	775	10,500	5.2	795	11,100				
	146 LWC	1.235	3.1	870	14,200	3.3	885	14,800	3.4	875	13,800	4.3	920	15,600	4.2	910	14,400	6.1	950	14,200				
	158 LRN	1.470	3.8	920	14,200	4.0	925	14,300	4.5	960	14,600	5.5	980	14,300	5.5	1,020	15,200	7.5	1,040	15,000	8.0	910	12,700	
	160 JSP	1.435	3.7	830	14,400	4.0	850	15,000	4.2	850	14,500	5.3	895	14,700	5.3	895	15,300	7.0	925	13,900	9.0	920	15,400	
.38 Long Colt	150 L	1.310	2.8	785	10,100	3.0	795	10,450	3.3	820	10,290	4.0	830	10,200	4.0	815	10,380							
.38 S&W	145 L	1.160	2.2	630	10,200	2.4	645	10,600	2.5	665	10,960	3.1	650	10,400	3.2	640	10,400							
.380 Auto.	88 JHP	0.960	3.2	980	14,300	3.1	965	14,600	3.4	940	14,600	4.0	920	13,600	4.1	995	14,900	6.0	1,000	14,700				
	90 JHP	0.960	3.0	940	12,900	3.1	940	14,300	3.2	890	12,800	4.0	940	14,000	4.0	960	14,800	6.0	980	14,800				
.41 Magnum	200 HP	1.580	8.0	1,235	35,700	7.5	1,200	33,400	8.5	1,270	35,300	10.5	1,370	35,700	10.1	1,320	35,900	14.0	1,470	36,000	17.5	1,420	34,700	
	210 JSP	1.575	8.3	1,245	34,300	8.3	1,235	33,400	9.0	1,280	35,800	10.8	1,365	35,200	10.5	1,340	34,500	13.5	1,425	33,800	17.5	1,425	33,900	
	220 JSP	1.575	7.5	1,150	35,800	7.5	1,145	35,900	8.0	1,155	35,700	9.5	1,235	35,200	9.3	1,220	35,800	12.5	1,365	35,800	16.4	1,365	34,300	
.44 S&W Special	180 JHC	1.600	6.5	910	12,000	7.0	915	11,700	8.0	975	12,600	9.5	1,010	12,600	10.0	1,050	12,600	13.5	1,020	11,900	16.0	950	11,400	
	246 L	1.590	4.5	765	11,700	4.9	775	11,500	6.5	805	11,700	6.5	805	11,200	8.0	825	12,000	9.2	845	12,300	11.3	805	11,500	
.44 Rem. Magnum	180 JHC	1.550	11.0	1,430	32,700	11.2	1,465	34,500	11.9	1,490	35,100	13.3	1,495	32,000	13.3	1,495	33,200	17.4	1,585	33,500	23.5	1,640	34,000	
	225 JHP	1.550	10.0	1,300	33,700	10.4	1,320	33,600	11.0	1,335	34,500	11.7	1,350	33,800	12.8	1,400	34,400	15.3	1,435	33,800	20.5	1,485	35,000	
	240 L(GC)	1.550	9.3	1,170	32,600	9.5	1,180	34,800	9.9	1,235	34,400	12.0	1,335	34,000	11.5	1,235	33,000	15.0	1,330	33,400	18.0	1,325	34,300	
	240 JSP	1.550	10.0	1,255	35,500	9.5	1,220	34,500	10.8	1,275	35,200	11.5	1,310	34,800	12.0	1,305	34,500	16.0	1,430	35,800	19.5	1,420	36,000	
	250 L	1.550	10.0	1,270	33,900	9.5	1,265	35,300	9.8	1,260	34,000	10.8	1,300	32,700	11.3	1,310	33,500	14.3	1,355	34,000	18.0	1,395	33,600	
	265 JFP	1.540	10.4	1,235	35,800	10.1	1,200	35,500	10.7	1,245	35,300	11.2	1,245	34,200	11.7	1,255	35,600	14.1	1,320	35,900	18.7	1,350	34,900	
.45 ACP Target Load	180 LWC	1.150	5.4	985	15,800	4.8	900	14,100	5.3	910	14,500	6.0	875	13,400	6.7	950	15,800	9.0	920	13,600				
	185 JHP	1.150	5.3	920	15,900	5.7	975	16,200	6.5	1,030	16,200	7.0	930	15,800	7.0	960	15,900	9.5	920	14,500				
	200 LSW	1.190	4.0	790	9,800	4.0	805	9,400	4.3	805	9,900	5.1	810	9,600										
	200 JHP	1.150	5.5	930	16,100	5.0	880	15,700	5.6	910	16,000	6.8	955	16,100	6.7	930	16,000	9.0	890	15,200				
	230 L	1.150	4.0	810	13,900	4.0	810	12,800	4.3	805	13,200	5.0	790	11,800	5.2	815	13,600							
	230 FMC	1.150	5.0	905	16,200	5.0	910	16,200	5.4	920	15,800	6.0	895	16,000	6.2	890	16,200	8.5	900	16,200				
.45 Colt	200 JMHP	1.570	6.0	870	11,800	7.0	915	12,600	8.0	940	12,500	9.0	895	11,600	9.5	895	11,400	13.0	925	11,800				
	250 L	1.570	5.4	805	11,800	6.0	830	12,000	6.8	855	12,300	8.0	850	11,800	9.0	910	12,600	11.5	890	12,200				

Notes:

- Do not intermix cases of different manufacture, nor bullets, nor primers.
- Be sure that each case is crack-free and completely empty.
- Use standard primers. Magnum primers are not needed nor recommended.

Key:

- | | | | | | |
|-----|---------------------|-----|----------------------|--------|------------------------|
| BR | = Bench Rest | PSI | = Chamber pressure, | gr. | = grains |
| FMC | = Full Metal Case | | piezo system | Vel. | = velocity |
| FMJ | = Full Metal Jacket | PSP | = Pointed Soft Point | fps | = feet per second |
| FN | = Flat Nose | RN | = Round Nose | c.w. | = powder charge weight |
| FP | = Flat Point | SB | = Solid Base | c.u.p. | = chamber pressure, |